

SPECIFICATIONS

TABLE SHIELDS: TABLE SHIELDS AND CONNECTOR CLIPS

Table Shields shall have the following construction standard features and benefits.

MODEL #
TABLE SHIELD

DIMENSIONS

FOR 12 FOOT TABLES

- MAIN PARTITION LENGTH: 71-¾"
- MAIN PARTITION HEIGHT: 23-½"
- THICKNESS: ¼"
- SMALLER PARTITION LENGTH: 29-½"
- SMALLER PARTITION HEIGHT: 23-½"
- THICKNESS: ¼"
- PRODUCT WEIGHT: 20 lbs.

FOR 10 FOOT TABLES

- MAIN PARTITION LENGTH: 59-½"
- MAIN PARTITION HEIGHT: 23-½"
- THICKNESS: ¼"
- SMALLER PARTITION LENGTH: 29-½"
- SMALLER PARTITION HEIGHT: 23-½"
- THICKNESS: ¼"
- PRODUCT WEIGHT: 20 lbs.

FOR 8 FOOT TABLES

- MAIN PARTITION LENGTH: 47-½"
- MAIN PARTITION HEIGHT: 23-½"
- THICKNESS: ¼"
- SMALLER PARTITION LENGTH: 29-½"
- SMALLER PARTITION HEIGHT: 23-½"
- THICKNESS: ¼"
- PRODUCT WEIGHT: 20 lbs.

FOR ROUND TABLES

- MAIN PARTITION LENGTH: 59-½"
- MAIN PARTITION HEIGHT: 23-½"
- THICKNESS: ¼"
- SMALLER PARTITION LENGTH: 29-½"
- SMALLER PARTITION HEIGHT: 23-½"
- THICKNESS: ¼"
- PRODUCT WEIGHT: 20 lbs.

TABLE SHIELD CONSTRUCTION

Table Shields shall be constructed of ¼" polycarbonate. Table Shields are held together with connector clips. Table Shields have rounded corners for safety.

CLIPS

Connector Clips are constructed of durable material.

CLEANING

Table Shields are easily cleaned with soap, water and non-abrasive cloth.

MAS GREEN CERTIFICATION

Table Shields shall be tested and certified for indoor air quality, for public safety as well as environmental protection.



UL

Table Shields shall be tested and listed by UL and must display UL labels with a valid listing marks.

WARRANTIES

Table Shields shall be covered by a Lifetime – Limited Lifetime Warranty.