


Endurance X-Base Table Installation



You will need:

Not Included:




1x
Pencil
For Marking Floor




1x
Drill
With 3/8" Masonry Bit



1x
Screwdriver
With Tamper Resistant Torx Bit




20x
3/8" - 16 x 4"
Tamper Resistant Torx
Anchor Bolt



20x
3/8" Flat Washer
.406" ID .875" OD


Included:




12x
5/16" Washer
.344" ID 1.25" OD



12x
5/16" - 18 x 2.5"
Security Torx Bolts




2x
Plastic Leg



1x
Table Top
Alternative Size & Shapes Available


Endurance X-Base Table Installation

1.




Drill through holes into the 10 bolt locations on the top of one of the leg pieces. Flip the leg over and drill through holes into the 10 bolt locations on the bottom of the leg. Repeat this process for the second leg.

2.




Slide the two leg pieces together using center slots.

3.



Flip table top over. Place assembled legs into pocket on bottom side of table top. Insert and tighten each table top screw 3-5 turns past finger tight.

4.



Turn over table, Position table in desired location. Using a pen or pencil, mark the leg mounting location onto the floor. Drill holes in the locations where you marked the center of the floor mount hole. Hole depth should be 2.0" deep MINIMUM. Install concrete anchor and bolt to table to floor.