

Fixed Shelf File (Model #FS350, 360, 351L, 361L) Specifications

Materials: Fixed Shelf Files as well as all Tennsco products are fabricated of high quality, cold rolled carbon steel, free of scale or rust and fully pickled. Exposed edges, corners and surface areas are free of sharp edges and all workmanship is of the highest quality as measured by the industry.

Finish: All steel components shall be thoroughly cleaned and phosphatized for rust resistance in a five-stage pre-treatment process. A high grade of polyester/epoxy powder paint is to be applied electrostatically with a gloss reading of between 55 and 65. The finish shall have a salt spray rating of 250 hours or more.

Back: 22 gauge, Offset and punched to accept file dividers.

Sides: 22 gauge, Channel formation on front.

Top: 20 gauge, Box formed cabinet top and bottom are assembled on the inside face of the side panels resulting in a side assembly with no outward seams.

Bottom: 20 gauge, Flanges on all four sides and punched for dividers.

Shelf: 20 gauge, Side flanges pop riveted to inner panel. Box formation at front. Punched to accept file dividers.

Door: Doors (12") lift up from the bottom, pivot on molded polyethylene door guides and recess into the cabinet above the shelf. The door opening and closing motion is guided by nylon buttons and a spring loaded "scissor" type equalizer. Both the open and closed position of the door is cushioned by rubber stops. Door has a painted steel long recessed pull handle located at the bottom of the door.

Gusset: 12 gauge, Two flanges for strength.

Leveling Glides: 4 per Unit.

Dividers: 20 gauge, 4 per shelf level.