

## Specifications

Mobile Rectangle Condiment Tables shall have the following construction standards, features and benefits.

**MODEL #:** CB2460, CB2472, CB2496, CB3060, CB3072, CB3096, CB3660, CB3672, CB3684

**DIMENSIONS:**

- **WIDTHS:** 24", 30", & 36"
- **LENGTH:** 5', 6', 7' & 8'
- **TABLE HEIGHT:** 29" OR 27"
- ADA models available

**FINISH**

Tables shall be finished with a powder paint coated frames and leg assemblies or nickel chrome plated leg assemblies or nickel chrome plated leg assemblies (for Chrome add 'C' to model number).

**TABLE TOPS**

*Choose one of the core materials and one of the edge protection choices.*

**PARTICLE BOARD**

3/4" thick, minimum 47# industrial grade particle board core **as standard**.

**Optional — PLYWOOD**

3/4" thick, premium grade plywood core with multiple plies for strength and durability (for Plywood add 'P' to model number).

**Optional — MDF**

3/4" thick, minimum 47# industrial grade medium density fiberboard core.

**DYNA-ROCK EDGE™ (DR)**

All cores listed above shall be permanently bonded with high pressure plastic laminate and balanced with a high pressure plastic laminate backing sheet to prevent moisture penetration. Top edges shall be sealed and protected with a 100% solid polyurethane resin sprayed and permanently bonded to the edges of the plastic laminate, core and plastic backing sheet **as standard**.

**FRAMES**

Table top shall be supported by a heavy-duty 14 gauge x 3" wide formed channel steel frame.

**LEGS**

Table legs shall be constructed of a heavy-duty 16 gauge X1-1/4" square steel tubing and 14 gauge, 2" x 1-1/2" rectangle steel tubing bottom caster beam.

**CASTERS**

Caster shall be 3" diameter by 1-3/8" wide, heavy-duty solid poly, non-marking wheels with a minimum rated load capacity of 275# each. All caster shall come standard with double raceway ball bearing swivel casters to help ensure years of safe operation. Tables with glides comes with heavy-duty, non-marking load bearing glides with floor leveler.

**OPERATIONAL ADVANTAGE:**

- The locking mechanism shall have an automatic spring loaded stop to lock table when folded down for use.
- Special High-Speed Gas Cylinder™ allows for easier and smoother operation of opening and closing.
- One-piece top prevents food from collecting within gaps, and allows for quick & easy cleaning before, during and after dining.
- 14 gauge, 3" steel frame shall support top in opened and closed position.
- Table design is versatile, allowing the table to be used within multiple environments and activities.
- Compact nesting and storage

**MAS GREEN CERTIFICATION**

Mobile table shall be tested and certified for indoor air quality, for public safety as well as environmental protection.

**WARRANTIES**

Mobile table shall be covered by a 15 year warranty.

All weld joints and DYNA-ROCK EDGES™ shall be covered by a lifetime warranty.



**CB2472DR**

