

Specifications

Mobile Folding Cafeteria EZ-Tilt™ Tables shall have the following construction standards, features and benefits.

MODELS: MRZT48, MRZT60 (Round); MSQZT60 (Square); MOCZT60 (Octagon); MOVZT72 (Oval)

DIMENSIONS

- **WIDTHS:** 48", 60", 60" x 72"
- **TABLE HEIGHT:** 29" OR 27"
- ADA models available

FINISH

Tables shall be finished with a powder paint coated frames and leg assemblies or nickel chrome plated leg assemblies (for Chrome add 'C' to model number).

TABLE TOP

Choose one of the core materials and one of the edge protection choices.

PARTICLE BOARD

3/4" thick, minimum 47# industrial grade particle board core **as standard**.

Optional — PLYWOOD

3/4" thick, premium grade plywood core with multiple plies for strength and durability (for Plywood add 'P' to model number).

Optional — MDF

3/4" thick, minimum 47# industrial grade medium density fiberboard core.

DYNA-ROCK EDGE™ (DR)

All cores listed above shall be permanently bonded with high pressure plastic laminate and balanced with a high pressure plastic laminate backing sheet to prevent moisture penetration. Top edges shall be sealed and protected with a 100% solid polyurethane resin sprayed and permanently bonded to the edges of the plastic laminate, core and plastic backing sheet **as standard**.

FRAMES

Table top shall be supported by heavy-duty 16 gauge, 2"x1" rectangle tubing and 14 gauge x 1" square steel tubing welded frame. Steel frame is reinforced with metal gussets for extra strength to maximize table top support.

LEGS

Table Legs shall be constructed of a heavy-duty 14 gauge x 1-1/16 round steel tubing.

OPERATIONAL ADVANTAGE:

- The locking mechanism shall have an automatic spring loaded safety stop to prevent table from being accidentally closed.
- Special High-Speed Gas Cylinder™ mechanism allows for easier and smoother operation of opening and closing.
- One-piece top prevents food from collecting within gaps, and allows for quick & easy cleaning before, during and after dining.
- Double steel frame shall support top in both opened and closed position.
- Compact nesting and storage

CASTERS

Caster shall be 4" diameter by 1-3/8" wide, heavy-duty solid poly, non-marking wheels with a minimum rated load capacity of 275# each. All caster shall come standard with double raceway ball bearing swivel casters to help ensure years of safe operation.

DYNAGRIP GLIDES™

Custom DYNAGRIP Glides™ are extra wide, high impact, non-marking, load bearing, glide with internal spring steel grip and steel washer for floor safety and wider support.

MAS GREEN CERTIFICATION

Mobile table shall be tested and certified for indoor air quality, for public safety as well as environmental protection.

WARRANTIES

Mobile table shall be covered by a 15 year warranty.

All weld joints and DYNA-ROCK EDGES™ shall be covered by a lifetime warranty.



MRZT60DR



Specifications

Mobile Folding Cafeteria EZ-Tilt Tables shall have the following construction standards, features and benefits.

Mobile Shape Table– One Piece Table Top

Octagon: 60" Dia. — Model #MOCZT60

TABLE HEIGHT: 29" OR 27"

FINISH

Tables shall be finished with powder coated frames and leg assemblies or chrome plated leg assemblies.

TABLE TOP

Choose one of the core material and edge protection choices:

1. PARTICLE BOARD (Standard)

3/4" thick, Min 47# industrial grade particle board as standard.

2. PLYWOOD (Optional)

3/4" thick, premium grade plywood with multiple plies for strength and durability.

3. MDF (Optional)

3/4" thick, min 47# industrial grade medium density fiberboard available upon request.

DYNA-ROCK EDGE™ (DR)

All cores listed above shall be permanently bonded with high pressure plastic laminate and balanced with a high pressure plastic laminate backing sheet to prevent moisture penetration. Top edges shall be sealed and protected with a 100% solid polyurethane resin sprayed and permanently bonded to the edges of the plastic laminate, core and plastic backing sheet.

*Vinyl edge available upon request.

FRAMES

Table top shall be supported by heavy duty 16 gauge, 2"x1" rectangle and 14 gauge x 1" Square steel tubular frame. Steel frame is reinforced with

metal gussets for extra strength and to maximize table top support.

LEGS

Table Legs shall be constructed of a heavy duty 14 gauge x 1-1/16 round steel tubing.

OPERATIONAL ADVANTAGE:

- The locking mechanism shall have an automatic spring loaded safety stop to prevent table from being accidentally closed.
- Special High speed Gas cylinder™ stabilizer allows for easier and smooth operation of opening and closing.
- One piece top prevents food from collecting in gaps and for ease of operation.
- Double steel frame shall support top in opened as well as closed position.

CASTERS

Caster shall be 4" diameter by 1 3/8" wide, heavy duty solid poly, non-marking wheels with a minimum rated load capacity of 275# each. All caster shall come standard with double raceway ball bearing swivel casters to help ensure years of safe operation.

DYNAGRIP GLIDES™

Custom DYNAGRIP glides™ are extra wide, high impact, non-marking, load bearing glide with internal spring steel grip and steel washer for floor safety and wider support

MAS GREEN CERTIFICATION

Mobile shape table shall be tested and certified for indoor air quality, for public safety as well as environmental protection.

WARRANTY

Mobile shape table shall be covered by a 15 year warranty.



MOCZT60

