

Specifications

Mobile Folding Cafeteria Rectangle Tables shall have the following construction standards, features and benefits.

MODELS: MT06, MT08, MT10, MT12, MT836, MT1036, MT1236, MT1046

DIMENSIONS

- **Height:** 29" OR 27"
- **Lengths:** 6'-1", 8'-1", 10'-1", 12'-1"
- **Widths:** 36" & 46"
- ADA models available

FINISH

Tables shall be finished with a powder paint coated frames and leg assemblies or nickel chrome plated leg assemblies (for Chrome add 'C' to model number).

TABLE TOP

Choose one of the core materials and one of the edge protection choices.

PARTICLE BOARD

3/4" thick, minimum 47# industrial grade particle board core **as standard**.

Optional — PLYWOOD

3/4" thick, premium grade plywood core with multiple plies for strength and durability (for Plywood add 'P' to model number).

Optional — MDF

3/4" thick, minimum 47# industrial grade medium density fiberboard core.

VINYL T-MOLDING

All cores listed above shall be permanently bonded with high pressure plastic laminate edging and balanced with a phenolic backing sheet to prevent moisture penetration **as standard**. Tops are edged with heavy-duty vinyl T-molding and fastened around the perimeter with staples.

Optional — DYNA-ROCK EDGE™ (DR)

All cores listed above shall be permanently bonded with high pressure plastic laminate and balanced with a high pressure plastic laminate backing sheet to prevent moisture penetration. Top edges shall be sealed and protected with a 100% solid polyurethane resin sprayed and permanently bonded to the edges of the plastic laminate, core and plastic backing sheet.

FRAMES

Table top shall be supported by heavy-duty 14 gauge, 3" wide formed channel steel frame.

LEGS

Table legs shall be constructed of a heavy-duty 14 gauge x 1-1/16" round and 1-1/4 **square steel tubing**. Caster mounting tube shall be 14 gauge x 1-1/4 **square steel tubing** for added strength and support.

OPERATIONAL ADVANTAGE

- **A gravity lock, rod and detent locking mechanism shall lock the table firmly in the open position and also shall be capable of operation from both sides of the table.**

CASTERS

Caster shall be 4" diameter by 1-3/8" wide, heavy-duty solid poly, non-marking wheels with a minimum rated load capacity of 275# each. All caster shall come standard with double raceway, ball bearing swivel casters to help ensure years of safe operation.

DYNAGRIP GLIDES™

Custom DYNAGRIP Glides™ are extra wide, high impact, non-marking, load bearing glide with internal spring steel grip and steel washer for floor safety and wider support.

CLEANING POSITION

Intermediate locking position allows for easy cleaning by raising the center of the table slightly until the casters contact the floor and lock the table.

EZ-AUTOLOCK™

Each table shall be furnished with a user friendly EZ-Autolocking™ system capable of locking the table automatically in the storage position and shall be easier to open for use by hand from either side of the table.

MAS GREEN CERTIFICATION

Mobile table shall be tested and certified for indoor air quality, for public safety as well as environmental protection.

UL

Tables shall be tested and listed by UL and must display UL labels with a valid listing marks.

WARRANTIES

Mobile table shall be covered by a 15 year warranty.

All weld joints and DYNA-ROCK EDGES™ shall be covered by a lifetime warranty.



MT12DR