

Ascent

80HS0106

SOVA

Universal Changing Table - 70"

The height-adjustable Sova Ascent Universal Changing Table redefines inclusion in public washrooms with its accessible design, intuitive features, simple wall-mount installation, and compact footprint. Made in the USA with limited imported components. Weight capacity: 500 lbs.



Product Dimensions:

Open: 70.25" L x 36.13" D x 69" H
Closed: 70.25" L x 9.75" D x 69" H

Product Weight:

400 lbs.

Adjustable Tray Heights:

16-39" H

Shipping Dimensions:

80.75" L x 47.75" W x 17.5" H

Shipping Weight:

490 lbs.

Weight Capacity:

500 lbs.

Features:

70" tray length meets IBC guidelines and accommodates adults while maintaining a compact footprint ideal for smaller restrooms

Engineered to mount to most existing walls

Convenient plug-in feature only requires a GFCI outlet / GFCI protected circuit for quick setup

Innovative automatic retracting feature stops operation and reverses direction when an obstruction is detected

Control buttons located front and side allow for easy height adjustments

Vacuum-formed ABS changing surface offers maximum usable space and is easy to clean

Direct attached actuator ensures superior performance, requiring minimal upkeep compared to chain-driven models

Entire unit is IPX6 rated, allowing for thorough and safe cleaning

Ascent

80HS0206

SOVA

Universal Changing Table - 76"

The height-adjustable Sova Ascent Universal Changing Table redefines inclusion in public washrooms with its accessible design, intuitive features, simple wall-mount installation, and compact footprint. Made in the USA with limited imported components. Weight capacity: 500 lbs.



Product Dimensions:

Open: 76.5" L x 41" D x 69" H
Closed: 76.75" L x 9.75" D x 69" H

Product Weight:

400 lbs.

Adjustable Tray Heights:

16-39" H

Shipping Dimensions:

80.75" L x 47.75" W x 17.5" H

Shipping Weight:

490 lbs.

Weight Capacity:

500 lbs.

Features:

76" tray accommodates adults with disabilities and meets IBC requirements

Engineered to mount to most existing walls

Convenient plug-in feature only requires a GFCI outlet / GFCI protected circuit for quick setup

Innovative automatic retracting feature stops operation and reverses direction when an obstruction is detected

Control buttons located front and side allow for easy height adjustments

Vacuum-formed ABS changing surface offers maximum usable space and is easy to clean

Direct attached actuator ensures superior performance, requiring minimal upkeep compared to chain-driven models

Entire unit is IPX6 rated, allowing for thorough and safe cleaning