



SECTION 10 28 14
DIAPER CHANGING STATION – 70HX0006

Sova offers a wide range of baby and adult changing stations meeting all applicable ASTM and A.D.A requirements when properly installed. Delete options and models not required for your project and modify to your project needs.

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Diaper changing stations.

1.2 SUBMITTALS

- A. Product Data: Manufacturer's data sheets on each product to be used, including:
 - 1. Preparation instructions and recommendations.
 - 2. Storage and handling requirements and recommendations.
 - 3. Installation methods.

1.3 DELIVERY, STORAGE, AND HANDLING

- A. Store products in manufacturer's unopened packaging until ready for installation.

1.4 PROJECT CONDITIONS

- A. Maintain environmental conditions (temperature, humidity, and ventilation) within limits recommended by manufacturer for optimum results. Do not install products under environmental conditions outside manufacturer's recommended limits.

1.5 WARRANTY

- A. Warranty: Provide manufacture's standard limited 5-year warranty. All warranties are effective from the date of initial shipment from manufacturer.

PART 2 PRODUCTS

2.1 MANUFACTURERS

- A. Acceptable Manufacturer: The Sova Company
- B. Substitutions: Not permitted.

2.2 DIAPER CHANGING STATIONS

- A. Diaper changing stations shall meet ASTM safety standards, include ANSI warning labels, and shall be ADA compliant when installed.
- B. Solace Extended Length, Special Needs Diaper Changing Station:
 - 1. Product: 70HR0006 – Solace Recessed Extended Length, Special Needs Stainless Steel Changing Station as manufactured by The Sova Company.
 - a. Rough-in dimensions for recessed unit: 63.25 inches W by 21.75 inches H (1607 mm W by 552 mm H).
 - b. Changing surface extends 17.875 inches (454 mm) from wall in open position.
 - c. Constructed of heavy-duty type 304 brushed stainless steel and is rated to support a static load of 400 lb (181 kg).
 - d. Replaceable high-hygiene ABS tray.
 - e. Dual pneumatic gas springs provide easy and safe open/close operation.
 - f. When closed, unit projects 1 inch (25 mm) from wall if recessed.
 - g. Features cushioned safety corners.
 - h. One-hand operation safety strap.
 - 2. Product: 70HS0006 - Solace Surface Mount Extended Length, Special Needs Stainless Steel Changing Station as manufactured by The Sova Company.
 - a. Required mounting surface 23.2 inches (588 mm) high by 64.4 inches (1636 mm) wide.
 - b. Changing surface extends 21.375 inches (543 mm) from wall in open position.
 - c. Constructed of heavy-duty type 304 brushed stainless steel and is rated to support a static load of 400 lb (181 kg).
 - d. Replaceable high-hygiene ABS tray.
 - e. Dual pneumatic gas springs provide easy and safe open/close operation.
 - f. When closed, unit projects 4 inches (102 mm) if surface mounted.
 - g. Features cushioned safety corners.
 - h. One-hand operation safety strap.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.

3.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

3.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions.

3.4 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

END OF SECTION