



SECTION 10 28 14
DIAPER CHANGING STATION – 30HX0106

Sova offers a wide range of baby and adult changing stations meeting all applicable ASTM and A.D.A requirements when properly installed. Delete options and models not required for your project and modify to your project needs.

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Diaper changing stations.

1.2 SUBMITTALS

- A. Product Data: Manufacturer's data sheets on each product to be used, including:
 - 1. Preparation instructions and recommendations.
 - 2. Storage and handling requirements and recommendations.
 - 3. Installation methods.

1.3 DELIVERY, STORAGE, AND HANDLING

- A. Store products in manufacturer's unopened packaging until ready for installation.

1.4 PROJECT CONDITIONS

- A. Maintain environmental conditions (temperature, humidity, and ventilation) within limits recommended by manufacturer for optimum results. Do not install products under environmental conditions outside manufacturer's recommended limits.

1.5 WARRANTY

- A. Warranty: Provide manufacture's standard limited 5-year warranty. All warranties are effective from the date of initial shipment from manufacturer.

PART 2 PRODUCTS

2.1 MANUFACTURERS

- A. Acceptable Manufacturer: The Sova Company
- B. Substitutions: Not permitted.

2.2 DIAPER CHANGING STATIONS

- A. Diaper changing stations shall meet ASTM safety standards, include ANSI warning labels, and shall be ADA compliant when installed.
- B. Vantage Stainless Steel Horizontal Changing Station:
 - 1. Product: 30HR0106 - Vantage Recessed Stainless Steel Horizontal Changing Station as manufactured by The Sova Company.
 - a. Rough-in dimension for recessed model is 35.625 inches W by 19.625 inches H (905 mm W by 499 mm H).
 - b. Changing surface extends 13.71 inches (349 mm) from wall in open position.
 - c. Constructed of heavy-duty type 304 brushed stainless steel.
 - d. Pneumatic gas spring provides easy and safe open/close operation.
 - e. One-hand operation safety strap.
 - f. Cushioned safety corners.
 - 2. Product: 30HS0106 - Vantage Surface Mount Stainless Steel Horizontal Changing Station as manufactured by The Sova Company.
 - a. Required mounting surface 21.875 inches (556 mm) high by 38.08 inches (968 mm) wide.
 - b. Changing surface extends 17.15 inches (436 mm) from wall in open position.
 - c. Constructed of heavy-duty type 304 brushed stainless steel.
 - d. Pneumatic gas spring provides easy and safe open/close operation.
 - e. One-hand operation safety strap.
 - f. Cushioned safety corners.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.

3.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

3.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions.

3.4 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

END OF SECTION



SECTION 10 28 14
DIAPER CHANGING STATION – 30HX0109

Sova offers a wide range of baby and adult changing stations meeting all applicable ASTM and A.D.A requirements when properly installed. Delete options and models not required for your project and modify to your project needs.

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Diaper changing stations.

1.2 SUBMITTALS

- A. Product Data: Manufacturer's data sheets on each product to be used, including:
 - 1. Preparation instructions and recommendations.
 - 2. Storage and handling requirements and recommendations.
 - 3. Installation methods.

1.3 DELIVERY, STORAGE, AND HANDLING

- A. Store products in manufacturer's unopened packaging until ready for installation.

1.4 PROJECT CONDITIONS

- A. Maintain environmental conditions (temperature, humidity, and ventilation) within limits recommended by manufacturer for optimum results. Do not install products under environmental conditions outside manufacturer's recommended limits.

1.5 WARRANTY

- A. Warranty: Provide manufacture's standard limited 5-year warranty. All warranties are effective from the date of initial shipment from manufacturer.

PART 2 PRODUCTS

2.1 MANUFACTURERS

- A. Acceptable Manufacturer: The Sova Company
- B. Substitutions: Not permitted.

2.2 DIAPER CHANGING STATIONS

- A. Diaper changing stations shall meet ASTM safety standards, include ANSI warning labels, and shall be ADA compliant when installed.
- B. Vantage Stainless Steel Horizontal Changing Station:
 - 1. Product: 30HR0109 - Vantage Recessed Stainless Steel Horizontal Changing Station as manufactured by The Sova Company.
 - a. Rough-in dimension for recessed model is 35.625 inches W by 19.625 inches H (905 mm W by 499 mm H).
 - b. Changing surface extends 13.71 inches (349 mm) from wall in open position.
 - c. Constructed of heavy-duty type 304 brushed stainless steel.
 - d. Pneumatic gas spring provides easy and safe open/close operation.
 - e. One-hand operation safety strap.
 - f. Cushioned safety corners.
 - 2. Product: 30HS0109 - Vantage Surface Mount Stainless Steel Horizontal Changing Station as manufactured by The Sova Company.
 - a. Required mounting surface 21.875 inches (556 mm) high by 38.08 inches (968 mm) wide.
 - b. Changing surface extends 17.15 inches (436 mm) from wall in open position.
 - c. Constructed of heavy-duty type 304 brushed stainless steel.
 - d. Pneumatic gas spring provides easy and safe open/close operation.
 - e. One-hand operation safety strap.
 - f. Cushioned safety corners.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.

3.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

3.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions.

3.4 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

END OF SECTION